

## RIDEMAX IT 696 - Specifiche tecniche



### Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	540/80 R 38 IND
LI/SS	172 A8/167 D

## Dimensions International Standard

Section Width (mm)	550
Overall Diameter (mm)	1829
Static Loaded Radius (mm)	833
Rolling Circumference (mm)	5537
SRI (mm)	875
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-004077

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2560	3160	3705	4305	4850	5450
50	2770	3415	4005	4655	5240	5890
40	2960	3655	4285	4975	5605	6300
30	3555	4385	5140	5970	6730	7560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/04/2025 06:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..