

RIDEMAX IT 696 - Scheda tecnica



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | TKPH | ECE |
|------------------------------------|----------|--------------|--------------------|-------------------------|-----|------|-----|------|-----|------|------|-----------------|
| 240/70 R 16 IND | STANDARD | 107A8/107B | W8 | W9 | 244 | 742 | 343 | 2226 | 350 | TL | | E11-106R-006942 |
| 340/80 R 18 IND | STANDARD | 143 A8/138 D | 11 ; 11 SDC ; W 11 | W 10 ; 12 ; 12 SDC | 343 | 1001 | 458 | 2980 | 475 | TL | | E11-106R-002987 |
| 360/80 R 20 IND | STANDARD | 143D/147A8 | 11 | W 10 ; W 11 ; 12 ; W 12 | 357 | 1084 | 488 | 3235 | 525 | TL | | E11-106R-007845 |
| 300/80 R 24 IND (11.2 R 24) | STANDARD | 133 A8/128 D | DW 10 | | 295 | 1090 | 501 | 3296 | 525 | TL | | E4-106R-002292 |
| 340/80 R 24 IND (12.4 R 24) | STANDARD | 140 A8/135 D | DW 11 | W 10 ; W 12 ; DW 10 | 343 | 1154 | 521 | 3444 | 550 | TL | | E4-106R-002293 |
| 360/80 R 24 IND (13.6 R 24) | STANDARD | 143 A8/138 D | DW 11 | W 12 ; W 10 | 343 | 1186 | 537 | 3556 | 575 | TL | | E11-106R-004753 |
| 400/80 R 24 IND (14.9 R 24) | STANDARD | 149 A8/144 D | DW 13 | W 12 ; W 14 L | 404 | 1250 | 558 | 3760 | 600 | TL | | E4-106R-002400 |
| 420/65 R 24 IND | STANDARD | 146 D/151 A8 | DW 13 L | DW 15 L ; DW 14 L | 418 | 1158 | 530 | 3483 | 550 | TL | 1 | E11-106R-005952 |
| 440/80 R 24 IND (16.9 R 24) | STANDARD | 154 A8/149 D | DW 14 L | DW 15 L ; DW 13 | 441 | 1314 | 590 | 3939 | 625 | TL | | E11-106R-004760 |
| 460/65 R 24 IND | STANDARD | 151 D/156 A8 | DW 14 L | DW 15 L ; DW 13 | 455 | 1214 | 549 | 3644 | 600 | TL | 1 | |
| 500/70 R 24 IND | STANDARD | 164A8/159D | DW 16 L | DW 15 L ; DW 18 L | 503 | 1310 | 602 | 3954 | 625 | TL | | E11-106R-007547 |
| 500/70 R 24 IND | STANDARD | 157 A8/152 D | DW 16 L | DW 15 L ; DW 18 L | 503 | 1310 | 602 | 3954 | 625 | TL | | E11-106R-007051 |
| 400/80 R 28 IND (14.9 R 28) | STANDARD | 151 A8/146 D | W 13 | W 12 ; W 14 L | 404 | 1352 | 615 | 4048 | 650 | TL | | E4-106R-002401 |
| 440/80 R 28 IND (16.9 R 28) | STANDARD | 156 A8/151 D | W 14 L | W 15 L | 441 | 1415 | 634 | 4288 | 675 | TL | | E4-106R-002299 |
| 440/80 R 30 IND (16.9 R 30) | STANDARD | 157 A8/153 D | W 14 L | W 15 L | 441 | 1466 | 668 | 4456 | 700 | TL | | E4-106R-002297 |
| 480/80 R 30 IND (18.4 R 30) | STANDARD | 162 A8/157 D | W 15 L | W 16 L | 479 | 1530 | 673 | 4558 | 725 | TL | | E4-106R-002298 |
| 440/80 R 34 IND (16.9 R 34) | STANDARD | 159 A8/155 D | DW 14 L | DW 15 L ; DW 16 L | 441 | 1567 | 704 | 4775 | 750 | TL | | E4-106R-002295 |
| 480/80 R 34 IND (18.4 R 34) | STANDARD | 164 A8/159 D | W 15 L | W 16 L | 479 | 1632 | 728 | 4894 | 775 | TL | | E4-106R-002296 |
| 480/80 R 38 IND (18.4 R 38) | STANDARD | 166 A8/161 D | W 15 L | W 16 L | 479 | 1733 | 780 | 5213 | 825 | TL | | E11-106R-004075 |
| 540/80 R 38 IND | STANDARD | 172 A8/167 D | W 18 L | W 16 L | 550 | 1829 | 833 | 5537 | 875 | TL | | E11-106R-004077 |
| 540/80 R 42 IND | STANDARD | 168 D/173 A8 | W 18 L | W 16 L | 560 | 1931 | 879 | 5875 | 925 | TL | | E11-106R-005714 |

Printed on 30/11/2023 03:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..