

## RIDEMAX IT 696 - Scheda tecnica



### Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
<b>240/70 R 16 IND</b>	STANDARD	94067503	107A8/107B	W8	W9	9.6	29.2	13.5	87.6	TL	0	E11-106R-006942
<b>340/80 R 18 IND</b>	STANDARD	94048960	143 A8/138 D	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.4	18	117.3	TL	0	E11-106R-002987
<b>360/80 R 20 IND</b>	STANDARD	94071074	143D/147A8	11	W 10 ; W 11 ; 12 ; W 12	14.1	42.7	19.2	127.4	TL	0	E11-106R-007845
<b>300/80 R 24 IND (11.2 R 24)</b>	STANDARD	94033881	133 A8/128 D	DW 10		11.6	42.9	19.7	129.8	TL	0	E4-106R-002292
<b>340/80 R 24 IND (12.4 R 24)</b>	STANDARD	94033843	140 A8/135 D	DW 11	W 10 ; W 12 ; DW 10	13.5	45.4	20.5	135.6	TL	0	E4-106R-002293
<b>360/80 R 24 IND (13.6 R 24)</b>	STANDARD	94057252	143 A8/138 D	DW 11	W 12 ; W 10	13.5	46.7	21.1	140	TL	0	E11-106R-004753
<b>400/80 R 24 IND (14.9 R 24)</b>	STANDARD	94038640	149 A8/144 D	DW 13	W 12 ; W 14 L	15.9	49.2	22	148	TL	0	E4-106R-002400
<b>420/65 R 24 IND</b>	STANDARD	94058464	146 D/151 A8	DW 13 L ; W13	DW 15 L ; DW 14 L	16.5	45.6	20.9	137.1	TL	1	E11-106R-005952
<b>440/80 R 24 IND (16.9 R 24)</b>	STANDARD	94057269	154 A8/149 D	DW 14 L	DW 15 L ; DW 13	17.4	51.7	23.2	155.1	TL	0	E11-106R-004760
<b>460/65 R 24 IND</b>	STANDARD	94058655	151 D/156 A8	DW 14 L	DW 15 L ; DW 13	17.9	47.8	21.6	143.5	TL	1	E11-106R-005109
<b>500/70 R 24 IND</b>	STANDARD	94067862	157 A8/152 D	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.7	155.7	TL	0	E11-106R-007051
<b>500/70 R 24 IND</b>	STANDARD	94070244	164A8/159D	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.7	155.7	TL	0	E11-106R-007547
<b>400/80 R 28 IND (14.9 R 28)</b>	STANDARD	94039227	151 A8/146 D	W 13	W 12 ; W 14 L	15.9	53.2	24.2	159.4	TL	0	E4-106R-002401
<b>440/80 R 28 IND (16.9 R 28)</b>	STANDARD	94034895	156 A8/151 D	W 14 L	W 15 L	17.4	55.7	25	168.8	TL	0	E4-106R-002299
<b>440/80 R 30 IND (16.9 R 30)</b>	STANDARD	94035816	157 A8/153 D	W 14 L	W 15 L	17.4	57.7	26.3	175.4	TL	0	E4-106R-002297
<b>480/80 R 30 IND (18.4 R 30)</b>	STANDARD	94033850	162 A8/157 D	W 15 L	W 16 L	18.9	60.2	26.5	179.4	TL	0	E4-106R-002298
<b>440/80 R 34 IND (16.9 R 34)</b>	STANDARD	94038657	159 A8/155 D	DW 14 L	DW 15 L ; DW 16 L	17.4	61.7	27.7	188	TL	0	E4-106R-002295
<b>480/80 R 34 IND (18.4 R 34)</b>	STANDARD	94035106	164 A8/159 D	W 15 L	W 16 L	18.9	64.3	28.7	192.7	TL	0	E4-106R-002296
<b>480/80 R 38 IND (18.4 R 38)</b>	STANDARD	94033867	166 A8/161 D	W 15 L	W 16 L	18.9	68.2	30.7	205.2	TL	0	E11-106R-004075
<b>540/80 R 38 IND</b>	STANDARD	94055838	172 A8/167 D	W 18 L	W 16 L	21.7	72	32.8	218	TL	0	E11-106R-004077
<b>540/80 R 42 IND</b>	STANDARD	94062409	168 D/173 A8	W 18 L	W 16 L	22	76	34.6	231.3	TL	0	E11-106R-005714

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..