

## RM 2002 - Specifiche tecniche



### Description

RM 2002 è uno pneumatico idoneo per le operazioni di trasporto con trailer e autocarri leggeri sia sulla strada che fuoristrada. Lo pneumatico assicura lunga durabilità ed elevate performance durante l'intero ciclo di vita del prodotto. La sua versione "industrial" è ideale per gru mobili "pick & carry".

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Rimorchio  
Industriale: Gru mobile

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	302
<b>Overall Diameter (mm)</b>	1101
<b>Rim Rec</b>	8.0
<b>Rim Alt</b>	7.5 ; 8.5

## Load capacity (Kg)

	km/h / bar	7.95	7.25
<b>100 LS</b>		3250	-
<b>100 LD</b>		-	2900

Printed on 25/04/2024 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..