

RM 500 - Specifiche tecniche



Description

RM 500 è uno pneumatico radiale con cinture in acciaio idoneo per applicazioni con attrezzi agricoli per mietitura. Lo pneumatico è dotato di una carcassa robusta e un particolare disegno del battistrada che offrono elevata capacità di carico e alta resistenza a tagli e lacerazioni. Grazie alla sua impronta larga, RM 500 garantisce l'ottima distribuzione della pressione sul terreno con ridotta compattazione del suolo, oltre a trazione eccellente.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Mietitrebbia

Version	STEEL BELTED
Type	TL
Tyre Size	500/85 R 24
LI/SS	182 A8 / 170 A8
LI/SS DRIVE WHEEL	170 A8
LI/SS FREE ROLLING	182 A8

Dimensions International Standard

Section Width (mm)	520
Overall Diameter (mm)	1460
Static Loaded Radius (mm)	622
Rolling Circumference (mm)	4382
SRI (mm)	700
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-005991

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
40 Free Rolling	3570	4335	5015	5780	6545	7055	7735	8500
40 Drive Wheel	2520	3060	3540	4080	4620	4980	5460	6000

Printed on 26/04/2024 07:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..