

ROCK GRIP E4 - Specifiche tecniche



Description

ROCK GRIP (E-4) è uno pneumatico a tele incrociate specificamente progettato per dumper rigidi impiegati nelle operazioni di miniera o di cava. Ogniqualvolta le vostre condizioni operative per i trasporti brevi sul sito richiedano sia resistenza al calore che protezione dai tagli, ROCK GRIP è il giusto pneumatico su cui fare affidamento.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	21.00 - 35

Dimensions International Standard

Ply Rating	36
Overall Width (mm)	580
Overall Diameter (mm)	2040
Static Loaded Radius (mm)	943
Rolling Circumference (mm)	6068
Rim Rec	15.00/3.0
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	7.50
50	12850	-
10	-	23000

Printed on 19/04/2024 20:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..