

ROCK GRIP E4 - Scheda tecnica



Description

ROCK GRIP (E-4) è uno pneumatico a tele incrociate specificamente progettato per dumper rigidi impiegati nelle operazioni di miniera o di cava. Ogniqualvolta le vostre condizioni operative per i trasporti brevi sul sito richiedano sia resistenza al calore che protezione dai tagli, ROCK GRIP è il giusto pneumatico su cui fare affidamento.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper rigido

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	E4	32	10.00/2.0		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	24	10.00/2.0		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	28	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	28	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	E4	28	10.00/2.0		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	28	10.00/2.0		375	1410	649	4173	TT
14.00 - 25	STANDARD	E4	32	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	24	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	E4	24	10.00/2.0		375	1410	649	4173	TT
14.00 - 25	STANDARD	E4	24	10.00/1.5		375	1410	649	4173	TT
16.00 - 25	STANDARD	E4	28	11.25/2.0	13.00/2.0	470	1525	699	4514	TL
16.00 - 25	STANDARD	E4	32	11.25/2.0	13.00/2.0	470	1525	699	4514	TL
18.00 - 25	STANDARD	E4	40	13.00/2.5	15.00/2.5	510	1650	753	4885	TL
18.00 - 25	STANDARD	E4	32	13.00/2.5	15.00/2.5	510	1650	753	4885	TL
18.00 - 25	STANDARD	E4	36	13.00/2.5	15.00/2.5	510	1650	753	4885	TL
18.00 - 25	STANDARD	E4	40	13.00/2.5	15.00/2.5	510	1650	753	4885	TT
18.00 - 25	STANDARD	E4	24	13.00/2.5	15.00/2.5	510	1650	753	4885	TT
18.00 - 25	STANDARD	E4	32	13.00/2.5	15.00/2.5	510	1650	753	4885	TT
18.00 - 33	CUT RESISTANT COMPOUND	E4	40	13.00/2.5		510	1887	869	5586	TL
18.00 - 33	CUT RESISTANT COMPOUND	E4	36	13.00/2.5		510	1887	869	5586	TL
18.00 - 33	STANDARD	E4	36	13.00/2.5		510	1887	869	5586	TT
18.00 - 33	STANDARD	E4	36	13.00/2.5		510	1887	869	5586	TL
18.00 - 33	STANDARD	E4	40	13.00/2.5		510	1887	869	5586	TT
18.00 - 33	STANDARD	E4	40	13.00/2.5		510	1887	869	5586	TL
18.00 - 33	STANDARD	E4	44	13.00/2.5		510	1887	869	5586	TL
21.00 - 35	CUT RESISTANT COMPOUND	E4	40	15.00/3.0		580	2040	943	6068	TL
21.00 - 35	CUT RESISTANT COMPOUND	E4	36	15.00/3.0		580	2040	943	6068	TL
21.00 - 35	STANDARD	E4	36	15.00/3.0		580	2040	943	6068	TL
21.00 - 35	STANDARD	E4	40	15.00/3.0		580	2040	943	6068	TL
24.00 - 35	CUT RESISTANT COMPOUND	E4	48	17.00/3.5		655	2190	1003	6482	TL
24.00 - 35	STANDARD	E4	48	17.00/3.5		655	2190	1003	6482	TL
24.00 - 49	CUT RESISTANT COMPOUND	E4	48	17.00/3.5		655	2531	1184	7498	TL
24.00 - 49	STANDARD	E4	42	17.00/3.5		655	2531	1184	7498	TL
24.00 - 49	STANDARD	E4	48	17.00/3.5		655	2531	1184	7498	TL
27.00 - 49	CUT RESISTANT COMPOUND	E4	48	19.50/4.0		740	2695	1253	7985	TL
27.00 - 49	CUT RESISTANT COMPOUND	E4	54	19.50/4.0		740	2695	1253	7985	TL
27.00 - 49	STANDARD	E4	54	19.50/4.0		740	2695	1253	7985	TL
27.00 - 49	STANDARD	E4	48	19.50/4.0		740	2695	1253	7985	TL
30.00 - 51	CUT RESISTANT COMPOUND	E4	52	22.00/4.5		830	2910	1350	8615	TL
30.00 - 51	STANDARD	E4	46	22.00/4.5		830	2910	1350	8615	TL
30.00 - 51	STANDARD	E4	52	22.00/4.5		830	2910	1350	8615	TL

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..