

ROCK GRIP IND4 (ECH) - Specifiche tecniche



Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) è uno pneumatico a tele diagonali progettato per movimentatori di container vuoti in diverse applicazioni tra cui movimentazione industriale e acciaierie. Lo speciale composto ROCK GRIP garantisce una particolare resistenza al calore, grande stabilità e durata nel tempo.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container vuoti

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	470
Overall Diameter (mm)	1525
Static Loaded Radius (mm)	699
Rolling Circumference (mm)	4514
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	16875

Printed on 20/04/2024 05:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..