

ROCK GRIP L4 - Scheda tecnica



Description

ROCK GRIP (L-4) è uno pneumatico a tele incrociate per pale gommate in operazioni di carico ardue su terreni insidiosi. La speciale miscela del battistrada è particolarmente resistente ad ogni tipo di tagli riducendo il rischio di foratura e quindi il tempo di fermo macchina. La profondità (L-4) del battistrada garantisce un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Dozer • Pala caricatrice

| SIZE | Version | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|----------|----------|----|-----------|---------|-----|------|-----|------|------|
| 14.00 - 25 | STANDARD | L4 | 24 | 10.00/1.5 | | 375 | 1410 | 649 | 4173 | TT |
| 14.00 - 25 | STANDARD | L4 | 24 | 10.00/1.5 | | 375 | 1410 | 649 | 4173 | TL |
| 14.00 - 25 | STANDARD | L4 | 28 | 10.00/1.5 | | 375 | 1410 | 649 | 4173 | TT |
| 14.00 - 25 | STANDARD | L4 | 28 | 10.00/1.5 | | 375 | 1410 | 649 | 4173 | TL |
| 14.00 - 25 | STANDARD | L4 | 32 | 10.00/1.5 | | 375 | 1410 | 649 | 4173 | TL |

Printed on 26/04/2024 20:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..