

ROCK STAR (SB SPL) - Specifiche tecniche



Description

ROCK STAR è stato particolarmente sviluppato per mezzi impiegati sia su strada che su rotaie in acciaio. ROCK STAR è uno pneumatico a 32 tele che offre elevata capacità di carico. La miscela unica del battistrada è particolarmente resistente a tagli e lacerazioni mentre le cinture in acciaio sono sinonimo di durabilità.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Veicolo strada-rotaia

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	390
Overall Diameter (mm)	1425
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Printed on 19/04/2024 20:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..