

RT 857 - Specifiche tecniche



Description

RT 857 è uno pneumatico progettato per la lavorazione del terreno. La carcassa robusta offre durabilità e trazione eccellenti. La miscela del battistrada è caratterizzata da un'elevata resistenza ad ogni tipo di taglio e alle stoppie.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 380/85 R 24 (14.9 R 24) |
| LI/SS | 131 A8/B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94053773 |
| Section Width (inch) | 15 |
| Overall Diameter (inch) | 49.4 |
| Static Loaded Radius (inch) | 22.3 |
| Rolling Circumference (inch) | 148.9 |
| Rim Rec | W 12 |
| Rim Alt | W 13 ; W 11 |
| ECE | E11-106R-002977 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 25 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 20 | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |
| 5 LT | 3170 | 3690 | 4210 | 4730 | 5250 | 5760 |
| 5 HT | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |

Printed on 20/04/2024 18:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..