

## RT 857 - Specifiche tecniche



### Description

RT 857 è uno pneumatico progettato per la lavorazione del terreno. La carcassa robusta offre durabilità e trazione eccellenti. La miscela del battistrada è caratterizzata da un'elevata resistenza ad ogni tipo di taglio e alle stoppie.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

## Dimensions US Standard

Usa code	94044566
Section Width (inch)	17.2
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	25.8
Rolling Circumference (inch)	173.1
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 13
ECE	E4-106R-001394
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3030	3530	4020	4520	5020	5510
25	3030	3530	4020	4520	5020	5510
20	3250	3780	4310	4840	5370	5900
5LT	4070	4730	5400	6060	6720	7390
5HT	3250	3780	4310	4840	5370	5900

Printed on 23/04/2024 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..