SIERRA MAX PRO - Specifiche tecniche

Description

SIERRA MAX PRO è il pneumatico BKT perfetto per applicazioni ATV, comprese le corse side-by-side. La sua costruzione radiale e la speciale impronta a terra più ampia offrono una guida più fluida, ottimizzando la trazione laterale e anteriore. Speciali ramponi robusti sono stati appositamente studiati per fornire un'eccellente trazione e una salda aderenza al terreno. Queste caratteristiche garantiscono una guida straordinariamente confortevole, offrendo sicurezza e controllo alla guida. SIERRA MAX PRO offre prestazioni eccellenti su ogni tipo di terreno, dai terreni duri ai terreni sciolti.

UM

US Standard

Construction

RADIAL

Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94066155
Section Width (inch)	11.2
Overall Diameter (inch)	27.9
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	84.4
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005098

Load capacity (lbs)

mph / psi	18
87	495

Printed on 29/04/2024 07:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..