

## SKID POWER ( CHEVRON ) - Specifiche tecniche



### Description

SKID POWER (CHEVRON) è stato sviluppato per pale skid steer nelle applicazioni per il settore costruzioni. Mostrando eccellente trazione insieme a proprietà avanzate di autopulitura, SKID POWER (CHEVRON) è particolarmente idoneo per superfici terrose, assicurando elevata resistenza a tagli e strappi.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	7.00 - 15

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	203
Overall Diameter (mm)	762
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2295
Rim Rec	5.50 F
Rim Alt	6 LB

## Load capacity (Kg)

km/h / bar	4.10
10	1440
15	1140

Printed on 25/04/2024 07:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..