

## SKID POWER SK - Specifiche tecniche



### Description

SKID POWER SK è stato particolarmente sviluppato per pale skid steer nelle applicazioni per il settore costruzioni. I cordoli di protezione del fianco e del cerchio nonché il battistrada extra profondo forniscono un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Pala Skid Steer

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	120 A8

## Dimensions US Standard

Usa code	94055715
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25
Rim Alt	
ECE	E11-106R-003544

## Load capacity (lbs)

mph / psi	75
25	3085

Printed on 23/04/2024 16:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..