

SKID POWER - Specifiche tecniche



Description

SKID POWER è stato sviluppato per pale skid steer nelle applicazioni dell'edilizia e mostra eccellente trazione insieme a proprietà avanzate di autopulitura. Lo pneumatico si distingue per il battistrada extra profondo insieme alla particolare protezione dei fianchi, assicurando eccellente resistenza a tagli e strappi oltre a straordinaria durabilità. SKID POWER è lo pneumatico ideale per superfici terrose.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94017133
Ply Rating	10
Section Width (inch)	12
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	95.4
Rim Rec	9.75

Load capacity (lbs)

mph / psi	65
5	5600
10	4420
15	4090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/01/2025 20:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..