

SKID POWER - Scheda tecnica



Description

SKID POWER è stato sviluppato per pale skid steer nelle applicazioni dell'edilizia e mostra eccellente trazione insieme a proprietà avanzate di autopulitura. Lo pneumatico si distingue per il battistrada extra profondo insieme alla particolare protezione dei fianchi, assicurando eccellente resistenza a tagli e strappi oltre a straordinaria durabilità. SKID POWER è lo pneumatico ideale per superfici terrose.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
25 X 8.5 - 14	STANDARD	106 A2	6	7 JA		213	652	305	1912	TL	E11-106R-006265
10 - 16.5	IMPLEMENT	116 A8	8	8.25		254	775	355	2286	TL	E11-106R-003534
10 - 16.5	STANDARD		8	8.25		254	775	355	2286	TL	
10 - 16.5	STANDARD		10	8.25		254	775	355	2286	TL	
12 - 16.5	IMPLEMENT	125 A8	10	9.75		305	821	373	2422	TL	E11-106R-003535
12 - 16.5	STANDARD		10	9.75		305	821	373	2422	TL	
14 - 17.5	IMPLEMENT	141 A8	14	10.5		355	940	424	2773	TL	E11-106R-003609
14 - 17.5	STANDARD		14	10.5		355	940	424	2773	TL	

Printed on 26/04/2024 18:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..