

SKID MAX SR-SKIDDER - Specifiche tecniche



Description

SKID MAX SR-SKIDDER è il nuovo pneumatico radiale BKT All Steel appositamente sviluppato per l'uso in ambienti di lavoro molto pesanti su superfici dure e migliorate come la manutenzione stradale e la discarica di rifiuti con minipale, terne e sollevatori telescopici. Grazie alla robusta carcassa in acciaio e alla costruzione della cintura, questo pneumatico offre una durata superiore e un'elevata capacità di carico.

Il robusto e ampio disegno del battistrada progettato con nervatura centrale continua, insieme a una miscela estremamente resistente all'abrasione e antistatica, garantisce un'ottima trazione e una lunga durata. La parete laterale extra spessa e la robusta carcassa garantiscono inoltre una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali, con conseguente diminuzione dei tempi di fermo macchina. La protezione del cerchio, appositamente progettata, protegge da forature e danni alle ruote nell'area del bordo del cerchio. Non dimenticare che SKID MAX SR-SKIDDER offre anche un comfort e una stabilità eccellenti durante il lavoro quotidiano.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Pala caricatrice • Pala Skid Steer • Sollevatore telescopico

Version	INDUSTRIAL
Type	TL
Tyre Size	260/70 R 16.5 (10 R 16.5)
LI/SS	129 A8/B

Dimensions International Standard

Overall Width (mm)	263
Overall Diameter (mm)	776
Static Loaded Radius (mm)	352
Rolling Circumference (mm)	2367
Rim Rec	8.25
Rim Alt	7.50 ; 9.00
ECE	E11-106R-006809

Load capacity (Kg)

km/h / bar	5.00
40	1850
50	1850

Printed on 18/04/2024 19:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..