

## SM 54 IND-4S - Specifiche tecniche



### Description

SM 54 IND-4S è stato appositamente progettato per i gestori di container vuoti reach stacker in applicazioni intermodali/logistiche. Presenta un'elevata stabilità in modalità di sollevamento e un design del battistrada profondo e regolare, offrendo un'eccellente resistenza al taglio per garantire un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

## Dimensions US Standard

Usa code	94015610
Ply Rating	28
Overall Width (inch)	16.9
Overall Diameter (inch)	57.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	171.4
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

## Load capacity (lbs)

mph / psi	131
5	34200

Printed on 26/04/2024 09:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..