

SM 54 IND-4S - Scheda tecnica



Description

SM 54 IND-4S è stato appositamente progettato per i gestori di container vuoti reach stacker in applicazioni intermodali/logistiche. Presenta un'elevata stabilità in modalità di sollevamento e un design del battistrada profondo e regolare, offrendo un'eccellente resistenza al taglio per garantire un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Reach Stacker

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.00 - 25	INDUSTRIAL	L45	28	11.25/2.0	13.00/2.0	430	1470	676	4354	TL
16.00 - 25	INDUSTRIAL	L45	32	11.25/2.0	13.00/2.0	430	1470	676	4354	TL

Printed on 26/04/2024 12:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..