

SM 54 M IND-4S - Specifiche tecniche



Description

SM 54 M IND-4S è la versione modificata del modello SM 54. Il profilo più piatto del battistrada si traduce in un'area di contatto più larga e assicura un ciclo di vita prolungato. Lo pneumatico è stato specificamente progettato per le unità di movimentazione per container vuoti e reach stacker nelle applicazioni intermodali e di logistica. SM 54 M si distingue per l'elevata stabilità in modalità di sollevamento nonché per il disegno profondo e liscio del battistrada che garantisce eccellente resistenza al taglio.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Reach Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94055791
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	192.1
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND-4S

Load capacity (lbs)

mph / psi	145
5	50600

Printed on 24/04/2024 22:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..