

## SM 55 IND-5S - Specifiche tecniche



### Description

SM 55 IND-5S è stato specificamente progettato per reach stacker e macchine per la movimentazione di container. La miscela speciale del battistrada, resistente all'abrasione, assicura una lunga vita dello pneumatico su superfici asfaltate o cementate, offrendo eccellente stabilità ai veicoli in modalità di sollevamento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Movimentatore per container

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

## Dimensions US Standard

Usa code	94060498
Ply Rating	20
Overall Width (inch)	12.2
Overall Diameter (inch)	50.2
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	148.7
Rim Rec	8.5
Rim Alt	7.33 V ; 8 ; 8.00 V ; 8.50 V
TRA Code	IND5

## Load capacity (lbs)

mph / psi	144
5	20540

Printed on 26/04/2024 16:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..