

SM 55 L5S - Specifiche tecniche



Description

SM 55 (L-5S) è uno pneumatico a tele incrociate ideale per le operazioni nelle miniere sotterranee. Il battistrada è realizzato con una speciale miscela resistente a tagli e strappi ed è caratterizzato da una profondità extra L-5S. Ciò si traduce in tempi ridotti di fermo macchina, garantendo una vita prolungata dello pneumatico. Lo pneumatico è anche disponibile in versione "steel belted" con cinture in acciaio.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper di basso profilo • Veicolo per miniere sotterranee

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	438
Overall Diameter (mm)	1375
Static Loaded Radius (mm)	631
Rolling Circumference (mm)	4043
Rim Rec	14.00/1.5
Rim Alt	14.00/1.3 ; 14.00/1.4 (DC)
TRA Code	L5S

Load capacity (Kg)

km/h / bar	6.75
10	9060
15	7880
25	7250

Printed on 26/02/2024 13:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..