

## SM 55 L5S - Specifiche tecniche



### Description

SM 55 (L-5S) è uno pneumatico a tele incrociate ideale per le operazioni nelle miniere sotterranee. Il battistrada è realizzato con una speciale miscela resistente a tagli e strappi ed è caratterizzato da una profondità extra L-5S. Ciò si traduce in tempi ridotti di fermo macchina, garantendo una vita prolungata dello pneumatico. Lo pneumatico è anche disponibile in versione "steel belted" con cinture in acciaio.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Dumper di basso profilo • Veicolo per miniere sotterranee

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.00 - 12 |

## Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94044986 |
| Ply Rating                   | 14       |
| Overall Width (inch)         | 8.1      |
| Overall Diameter (inch)      | 28       |
| Static Loaded Radius (inch)  | 12.7     |
| Rolling Circumference (inch) | 85       |
| Rim Rec                      | 5.00 S   |
| TRA Code                     | L5S      |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 131  |
| 15        | 4670 |

Printed on 20/04/2024 08:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..