

## SNOW - RIDE (A) - Specifiche tecniche



### Description

SNOW-RIDE è particolarmente idoneo per applicazioni comunali/manutenzione in condizioni invernali con pale compatte e pale skid steer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazioni su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento e garantisce un ciclo prolungato dello pneumatico.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pala compatta  
Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions US Standard

Usa code	94044009
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	92.1
Rim Rec	8.25

## Load capacity (lbs)

mph / psi	75
5	4710

Printed on 09/05/2024 13:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..