

SNOW - RIDE (A) - Specifiche tecniche



Description

SNOW-RIDE è particolarmente idoneo per applicazioni comunali/manutenzione in condizioni invernali con pale compatte e pale skid steer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazioni su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento e garantisce un ciclo prolungato dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta
Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	15.5/60 - 18

Dimensions US Standard

Usa code	94041398
Ply Rating	10
TMPH	1
Section Width (inch)	15.6
Overall Diameter (inch)	36.9
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	110.8
Rim Rec	W 13
ECE	'E11-106R-005302

Load capacity (lbs)

mph / psi	38
5	5290

Printed on 09/05/2024 06:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..