

SNOW - RIDE (A) - Specifiche tecniche



Description

SNOW-RIDE è particolarmente idoneo per applicazioni comunali/manutenzione in condizioni invernali con pale compatte e pale skid steer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazioni su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento e garantisce un ciclo prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	17.5/65 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	445
Overall Diameter (mm)	1095
Static Loaded Radius (mm)	493
Rolling Circumference (mm)	3285
Rim Rec	W 14 L

Load capacity (Kg)

km/h / bar	2.40
10	3195

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 07:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..