

SNOW - RIDE (A) - Scheda tecnica



Description

SNOW-RIDE è particolarmente idoneo per applicazioni comunali/manutenzione in condizioni invernali con pale compatte e pale skid steer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazioni su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento e garantisce un ciclo prolungato dello pneumatico.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pala compatta
Industriale: Pala Skid Steer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
12.5/70 - 16	STANDARD	94040575	6	10 LB		12.4	33.5	15.2	100.4	TL	1	
12.5/70 - 16	STANDARD	94044023	10	10 LB		12.4	33.5	15.2	100.4	TL	1	
10 - 16.5	STANDARD	94040261	6	8.25		10.6	30.7	14.1	92.1	TL	0	
10 - 16.5	STANDARD	94044009	10	8.25		10.6	30.7	14.1	92.1	TL	0	
12 - 16.5	STANDARD	94043330	6	9.75	-	12	32.9	14.9	98.6	TL	0	
12 - 16.5	STANDARD	94044016	10	9.75	-	12	32.9	14.9	98.6	TL	0	
15.5/60 - 18	STANDARD	94041398	10	W 13		15.6	36.9	16.7	110.8	TL	1	'E11-106R-005302
17.5/65 - 20	STANDARD	94041381	10	W 14 L		17.5	43.1	19.4	129.3	TL	0	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 08:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..