

## SNOW - RIDE (B) - Specifiche tecniche

### Description

SNOW-RIDE è particolarmente idoneo per applicazioni su strada in condizioni invernali con macchine loader e dozer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazione su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Dozer • Pala caricatrice



Version	STANDARD
Type	TL
Tyre Size	18.4 - 24

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>TKPH</b>	1
<b>Section Width (mm)</b>	475
<b>Overall Diameter (mm)</b>	1375
<b>Static Loaded Radius (mm)</b>	625
<b>Rolling Circumference (mm)</b>	4089
<b>SRI (mm)</b>	650
<b>Rim Rec</b>	DW 16 L
<b>Rim Alt</b>	DW 15 L

## Load capacity (Kg)

km/h / bar	2.50
40	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/03/2025 12:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..