

## SNOW - RIDE (B) - Specifiche tecniche

### Description

SNOW-RIDE è particolarmente idoneo per applicazioni su strada in condizioni invernali con macchine loader e dozer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazione su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Dozer • Pala caricatrice



Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

## Dimensions US Standard

Usa code	94044399
Ply Rating	16
Section Width (inch)	21.1
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	174.1
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	L2

## Load capacity (lbs)

mph / psi	51
5	18200

Printed on 23/04/2024 13:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..