

SNOW - RIDE (B) - Specifiche tecniche

Description

SNOW-RIDE è particolarmente idoneo per applicazioni su strada in condizioni invernali con macchine loader e dozer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazione su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Dozer • Pala caricatrice



Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions International Standard

Ply Rating	16
Section Width (mm)	612
Overall Diameter (mm)	1630
Static Loaded Radius (mm)	693
Rolling Circumference (mm)	4800
Rim Rec	19.50/2.5
TRA Code	L2

Load capacity (Kg)

km/h / bar	3.00
10	9500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/03/2025 06:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..