

SNOW - RIDE (B) - Scheda tecnica

Description

SNOW-RIDE è particolarmente idoneo per applicazioni su strada in condizioni invernali con macchine loader e dozer. Lo pneumatico si distingue per l'eccellente trazione ed è ideale per operazione su neve e ghiaccio. Il disegno speciale del battistrada elimina i rischi di slittamento.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Dozer • Pala caricatrice



SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH
16.9 - 24	STANDARD	94043439		12	DW 15 L	DW 14 L	16.9	51.6	23.2	154.7	TL	1
18.4 - 24	STANDARD	94044054		12	DW 16 L	DW 15 L	18.7	54.1	24.6	161	TL	1
15.5 - 25	STANDARD	94048625	L2	12	12.00/1.3		15.6	50.4	22.4	150.3	TL	0
17.5 - 25	STANDARD	94054138	L2	16	14.00/1.5		17.5	53.1	23.9	159.2	TL	0
17.5 - 25	STANDARD	94043446	L2	12	14.00/1.5		17.5	53.1	23.9	159.2	TL	0
20.5 - 25	STANDARD	94044399	L2	16	17.00/2.0	17.00/1.7	21.1	58.7	25.7	174.1	TL	0
23.5 - 25	STANDARD	94047918	L2	16	19.50/2.5		24.1	64.2	27.3	189	TL	0

Printed on 23/04/2024 16:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..