

ST 180 - Specifiche tecniche



Description

ST 180 è uno pneumatico sviluppato per applicazioni di trasporto con rimorchi e attrezzi agricoli. Il disegno specifico del battistrada riduce l'usura, garantendo un ciclo di vita lungo dello pneumatico. ST 180 è disponibile in tre versioni: una versione "aramid belted" con cinture in aramide assicura maggiore resistenza alla perforazione, mentre la versione "special" garantisce elevata resistenza a tagli e lacerazioni.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	4.80 - 8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	121
Overall Diameter (mm)	418
Rim Rec	3.75 - I - 55
Rim Alt	3.75 - I - 70

Load capacity (Kg)

km/h / bar	6.20
100	345

Printed on 06/12/2023 02:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..