

## ST 180 - Scheda tecnica



### Description

ST 180 è uno pneumatico sviluppato per applicazioni di trasporto con rimorchi e attrezzi agricoli. Il disegno specifico del battistrada riduce l'usura, garantendo un ciclo di vita lungo dello pneumatico. ST 180 è disponibile in tre versioni: una versione "aramid belted" con cinture in aramide assicura maggiore resistenza alla perforazione, mentre la versione "special" garantisce elevata resistenza a tagli e lacerazioni.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.80 - 8	STANDARD	94008759	6	3.75 - I - 55	3.75 - I - 70	4.8	16.5	0	0	TL	
5.70 - 8	STANDARD	94027897	6	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	5.6	18.7	0	0	TL	
5.70 - 8	STANDARD	94008797	8	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	5.6	18.7	0	0	TL	
6.00 - 9	STANDARD	94038343	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022804
6.00 - 9	STANDARD	94038350	10	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022805
6.00 - 9	STANDARD	94026623	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TT	E4-54R-0022806
6.00 - 9	STANDARD	94038367	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022806
6.00 - 9	STANDARD	94008827	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TT	E4-54R-0022804
5.00 - 10	STANDARD	94043002	6	3.5		5.6	20.9	0	0	TL	E4-54R-0030484
ST 165/80 D 13 (A 78 - 13)	STANDARD	94018079	4	4½ J	5 J ; 5½ J ; 6 J	6.1	23.5	10.7	68.7	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018086	4	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018093	6	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018109	8	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018116	4	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018123	6	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018130	8	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 205/65 D 14 (F 65 - 14)	STANDARD	94018147	6	5 J	5½ J	7.5	24.4	11.5	73.8	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	94018161	4	6 J	5 J ; 5½ J ; 6 J	7.9	26.9	12.5	80.7	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	94018178	6	6 J	5 J ; 5½ J ; 6 J	7.9	26.9	12.5	80.7	TL	
ST 215/75 D 14 (G 78 - 14)	ARAMID BELTED	94053018	10	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 215/75 D 14 (G 78 - 14)	SPECIAL	94052943	10	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 215/75 D 14 (G 78 - 14)	STANDARD	94018208	6	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 205/65 D 15 (F 65 - 15)	STANDARD	94018154	6	6 J	5½ J ; 6½ J	7.6	25.5	11.9	76.2	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	94018185	4	5½ J	5 J ; 6 J ; 7 J	7.7	27.6	12.9	82.8	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	94018192	6	5½ J	5 J ; 6 J ; 7 J	7.7	27.6	12.9	82.8	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	94018215	6	6 J	5½ J ; 6½ J ; 7 J	8.5	28.7	13.3	85.7	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	94018222	8	6 J	5½ J ; 6½ J ; 7 J	8.5	28.7	13.3	85.7	TL	

Printed on 03/12/2023 05:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part,

