

## STEER FARM - Specifiche tecniche



### Description

STEER FARM è stato progettato per trattori 2WD/2RM nelle applicazioni di lavorazione del terreno e offre eccellenti prestazioni di sterzata.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	98 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	185
Overall Diameter (mm)	770
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E4-106R-002187
TRA Code	F2

## Load capacity (Kg)

km/h / bar	4.20
30	750

Printed on 24/04/2024 07:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..