

STEER FARM - Specifiche tecniche



Description

STEER FARM è stato progettato per trattori 2WD/2RM nelle applicazioni di lavorazione del terreno e offre eccellenti prestazioni di sterzata.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	805
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2451
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E11-106R-003547
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	875

Printed on 04/05/2024 01:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..