

STEER GRIP - Specifiche tecniche



Description

STEER GRIP è l'equipaggiamento ideale per le assi sterzanti di autocarri con cassone ribaltabile. La larga nervatura centrale con ramponi lineari rende lo pneumatico idoneo per applicazioni free rolling, garantendo eccellenti prestazioni sia in condizioni bagnate che asciutte fuori strada. La speciale mescola del battistrada è stata realizzata per abbinare ottima resistenza all'usura e resistenza a tagli e lacerazioni, mentre la carcassa robusta assicura un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	310
Overall Diameter (mm)	1248
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3785
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 26/04/2024 20:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..