

SUPER GRADER - Specifiche tecniche



Description

SUPER GRADER (G-2) è uno pneumatico diagonale particolarmente sviluppato per motolivellatrici, che mostra eccellente trazione ed ottime proprietà di autopulitura. SUPER GRADER è stato realizzato con una miscela speciale che consente un ciclo di vita prolungato dello pneumatico e l'impiego in servizi pesanti.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motolivellatrice

Version	STANDARD
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94014514
Ply Rating	16
Overall Width (inch)	14.3
Overall Diameter (inch)	52.6
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	155.6
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

Load capacity (lbs)

mph / psi	51
25	8050

Printed on 25/04/2024 16:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..