

SUPER SAND - Specifiche tecniche



Description

SUPER SAND è particolarmente idoneo per rimorchi che operano su superfici sabbiose in condizioni climatiche calde. Lo pneumatico si distingue per l'elevata capacità di galleggiamento ed è ideale per tutte le operazioni che richiedono un elevato livello di manipolazione.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	16.00 - 20

Dimensions US Standard

Usa code	94048359
Ply Rating	16
Section Width (inch)	16.3
Overall Diameter (inch)	51.4
Rim Rec	10.00 W

Load capacity (lbs)

	mph / psi	36
	30	8050

Printed on 23/04/2024 18:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..