

## TF 8181 - Specifiche tecniche



### Description

TF 8181 è uno pneumatico per l'impiego su campo e su strada sviluppato per trattori 2WD/2RM nelle applicazioni di lavorazione del terreno e di trasporto. Questo pneumatico assicura elevate prestazioni di sterzata.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore 2WD  
Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS	73 A6

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	142
Overall Diameter (mm)	655
Static Loaded Radius (mm)	307
Rolling Circumference (mm)	1951
Rim Rec	4.00 E
Rim Alt	3.00 D ; 4 J ; 4½ J
TRA Code	F2

## Load capacity (Kg)

km/h / bar	2.80
30	365

Printed on 19/04/2024 18:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..