

## TF 9090 - Specifiche tecniche



### Description

TF 9090 è uno pneumatico progettato per trattorini nelle operazioni di lavorazione della terra. Il particolare disegno del battistrada garantisce un ottimo controllo di sterzata su terreno sciolto.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattorino  
Industriale: Rimorchio

Version	SPECIAL
Type	TT
Tyre Size	10.00 - 16
LI/SS	111 A8

## Dimensions US Standard

Usa code	94038848
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	106.9
Rim Rec	W 8
Rim Alt	W 8 L
ECE	E11-106R-004418
TRA Code	F2

## Load capacity (lbs)

mph / psi	50
25	2400

Printed on 02/12/2023 20:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..