

## TF 9090 - Specifiche tecniche



### Description

TF 9090 è uno pneumatico progettato per trattorini nelle operazioni di lavorazione della terra. Il particolare disegno del battistrada garantisce un ottimo controllo di sterzata su terreno sciolto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattorino  
Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	86 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	150
Overall Diameter (mm)	710
Static Loaded Radius (mm)	332
Rolling Circumference (mm)	2116
Rim Rec	4.00 E
Rim Alt	3.50 D ; 4.50 E
ECE	E4-106R-001955
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.70
30	530

Printed on 27/04/2024 07:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..