

## TF 9090 - Specifiche tecniche



### Description

TF 9090 è uno pneumatico progettato per trattorini nelle operazioni di lavorazione della terra. Il particolare disegno del battistrada garantisce un ottimo controllo di sterzata su terreno sciolto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattorino  
Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	7.50 - 18
LI/SS	101 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	207
Overall Diameter (mm)	860
Static Loaded Radius (mm)	404
Rolling Circumference (mm)	2562
Rim Rec	5.50 F
ECE	E11-106R-004317
TRA Code	F2

## Load capacity (Kg)

km/h / bar	2.80
30	825

Printed on 27/04/2024 05:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..