

TR 117 - Specifiche tecniche



Description

TR 117 è ideale per applicazioni di irrigazione con pivot centrale. Il particolare disegno del battistrada garantisce eccellente trazione nonché straordinarie proprietà di autopulitura.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Irrigatore a pivot

Version	STANDARD
Type	TL
Tyre Size	11.2 - 24
LI/SS	101 A6

Dimensions International Standard

Ply Rating	4
Section Width (mm)	284
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	509
Rolling Circumference (mm)	3205
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-001966
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.20	1.55
30	825	---
CREEP	---	1585

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Printed on 24/04/2024 15:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..