

## TR 117 - Specifiche tecniche



### Description

TR 117 è ideale per applicazioni di irrigazione con pivot centrale. Il particolare disegno del battistrada garantisce eccellente trazione nonché straordinarie proprietà di autopulitura.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Irrigatore a pivot

Version	STANDARD
Type	TT
Tyre Size	11.2 - 38
LI/SS	106 A8

## Dimensions US Standard

Usa code	94028801
Ply Rating	4
Section Width (inch)	11.2
Overall Diameter (inch)	56.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	173.2
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-002747
TRA Code	R1

## Load capacity (lbs)

mph / psi	18	25
25	2090	---
CREEP	---	4420

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN )

Printed on 24/04/2024 16:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..