

TR 118 - Scheda tecnica



Description

TR 118 è stato progettato per macchine irroratrici. TR 118 si distingue per la carcassa rinforzata e un maggior numero di tasselli che assicurano una vita operativa più lunga dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Irrigatore a pivot

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.9 - 24	STANDARD	94052363	R1	124 A8	8	W 13	W 12 ; W 11	15	49.8	22.3	147.3	TL	E11-106R-004420

Printed on 26/04/2024 10:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..