

## TR 126 - Specifiche tecniche



### Description

TR 126 è stato sviluppato per trattorini nelle operazioni di lavorazione della terra. I ramponi profondi e il particolare disegno del battistrada offrono eccellente trazione e straordinaria capacità di carico che si traducono in elevatissime prestazioni in tutte le condizioni operative.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattorino

Version	STANDARD
Type	TL
Tyre Size	7 - 14
LI/SS	72 A6

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	170
Overall Diameter (mm)	690
Static Loaded Radius (mm)	320
Rolling Circumference (mm)	2070
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-003356
TRA Code	R1

## Load capacity (Kg)

km/h / bar	1.60
30	355

Printed on 20/04/2024 14:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..