

TR 126 - Specifiche tecniche



Description

TR 126 è stato sviluppato per trattorini nelle operazioni di lavorazione della terra. I ramponi profondi e il particolare disegno del battistrada offrono eccellente trazione e straordinaria capacità di carico che si traducono in elevatissime prestazioni in tutte le condizioni operative.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattorino

Version	STANDARD
Type	TT
Tyre Size	7 - 14
LI/SS	92 A8

Dimensions US Standard

Usa code	94052639
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	12.6
Rolling Circumference (inch)	81.5
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-005233
TRA Code	R1

Load capacity (lbs)

mph / psi	58
25	1390

Printed on 20/04/2024 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..