

## TR 128 - Specifiche tecniche



### Description

TR 128 è stato particolarmente sviluppato per trattori compatti e coltivatori rotativi. Il disegno largo e profondo dei ramponi e la speciale miscela resistente a tagli e lacerazioni assicurando una vita prolungata dello pneumatico. TR 128 si distingue per la massima trazione sul terreno bagnato.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Coltivatore rotativo • Veicolo universale

Version	STANDARD
Type	TT
Tyre Size	5 - 12
LI/SS	60 A8

## Dimensions US Standard

Usa code	94055883
Ply Rating	6
Section Width (inch)	5
Overall Diameter (inch)	21.8
Static Loaded Radius (inch)	10.3
Rolling Circumference (inch)	66.9
Rim Rec	4 JA
ECE	E11-106R-005189

## Load capacity (lbs)

mph / psi	52
25	550

Printed on 17/04/2024 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..