

TR 133 - Scheda tecnica



Description

TR 133 è stato specialmente progettato per trattori nelle applicazioni di lavorazione della terra. Grazie al numero maggiore di ramponi, lo pneumatico si distingue per l'eccellente trazione e lo straordinario comfort nonché le proprietà di autopulitura avanzate. TR 133 garantisce un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
13.6 - 38 (14.00 - 38)	STANDARD	R1	136 A6	10	W 12	W 11	350	1580	735	4843	750	TT	E11-106R-003549

Printed on 25/04/2024 05:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..